

G.H. Infield Maintenance

Main goal to ensure infield mix is not moved under the turf.

Always rake pulling material away from turf edge.

- Do not rake infield material onto or towards turf.
- When using broom on J.S.F. diamond between 1st and 3rd, always stay a minimum of 12” from turf edge. When finishing turf edge, flip metal rake upside down, using blade at a 45-degree angle, to move material away from edge of turf.
- When raking running paths, between home-1st + home-3rd. Always stand on one side of the track and reach across to turf edge and drag material to the middle. Once you complete one side, repeat on the other side of the track. Same drill for the teardrop in front of the mound. Finish by running rake down centre of path.
- Edge of turf may be raked or swept onto running track to reduce build up lip of infield material.
- When using hose, please ensure the nozzle is set to spray. Do not spray towards edge of turf. When needed dampen down running tracks to reduce dust and allow material to be tamped into low spots.
- Fill and tamp any low spots paying attention to the wear areas around and in front of bases, home plate and bull pens. The filled areas may need to be sprayed down and tamped to help prevent low spots from reforming quickly.

Mound Maintenance

- Hand rake mound and fill any holes or depressions.
- Tamp material into holes (damp material tamps better).
- If hole develops in front of the pitching rubber. Contact me and I will assist with installing Turface bricks.

Thank You